

UP/UP-K Faceplate 1x, 2x, 3x

flush/duct mounted

for 1, 2 or 3 modules with Keystone fitting, angled outlet



GERMAN STANDARD



1



2



3

- 1 1-port faceplate, angled outlet
- 2 2-port faceplate, angled outlet

- 3 3-port faceplate, angled outlet

DESCRIPTION

Faceplates applicable for the installation of 1, 2 or 3 modules with Keystone fitting. The modules are easily fitted into the faceplates. Integrated dust shutters. The central plate has a labelling field with transparent cover. On metallic support frame, an additional grounding connection is available. Delivered without modules.

APPLICATION

Suitable for the following Datwyler modules:

- PS-GG45 7_A 4P shielded
- RJ45 module KS-T Plus 1/8 Cat. 6_A shielded
- RJ45 module KU Plus 1/8 Cat. 6_A unshielded
- RJ45 module KS-TS 1/8 Cat. 6/E_A shielded
- RJ45 module KS-T 1/8 Cat. 6/E_A shielded
- RJ45 module KU-T 1/8 Cat. 6 / Cat. 5e unshielded

DIMENSIONS

Faceplates	German standard
Mounting plate	70 x 70 mm
Central plate	50 x 50 mm
Cover frame	80 x 80 mm

NOTE

3-port faceplate not compatible with switch range (designs) of other vendors.

VERSIONS

Article No.	Standard	Product	Colour (similar to)	PU
185866	DE	UP-K Faceplate for 1 module with Keystone snap-in fitting, angled	pure white, RAL 9010	1 pc.
185867	DE	UP-K Faceplate for 2 modules with Keystone snap-in fitting, angled	pure white, RAL 9010	1 pc.
185869	DE	UP-K Faceplate for 3 modules with Keystone snap-in fitting, angled	pure white, RAL 9010	1 pc.